




36040 Meledo di Sarego (Vi) ITALIA

Tel. +390444-820044 Fax +390444-820050

www.bericacavi.com e-mail: bericacavi@bericacavi.com

Cable for security systems, Al/Pet tape screen, halogen free.

Comari Alarmkabel massief afgeschermd

Features	Description	Standards
Conductors :	annealed red copper cl.1	
Insulation :	LSZH compound	
Cores colour :	2x(Black-Red); 4x(Blue-Red-Green-Yellow); 6x(Blue-Red-Yellow-Green-White-Black) 8x(Blue-Red-Yellow-Green-White-Black-Grey-Brown)	
Assembling :	Pet tape	
Drain wire :	annealed red copper 1x0,50 mm	
Screen :	Al/Pet tape	
Sheath :	LSZH compound , M1 type	CEI EN 50363
Sheath colour :	white RAL 9010 or red RAL 3000	
Halogen free :	(< 0,5 mg/g - 0,5%)	CEI EN 50267-2-1/2 - IEC 60754-1/2
Rated voltage Uo/U:	300/300 V	
Max voltage :	330 V	
Testing voltage :	2000 V	
Max working temperature :	70 °C	
Short-circuit temperature :	160 °C	
Min. installation temperature :	0 °C	
Bending radius :	Ø x 8	

APPLICATION : Used in intrusion detection systems.**INSTALLATION :** For fixed indoor installations in dry or temporarily wet environments and temporarily outdoor. They can be installed on platforms, pipes, conduits and similar systems. Not for direct burial.

Type (N° cores x Ø)						Medium Ø outer	Medium weight	Product code
N° x mm						mm	kg x km	
8x0,50						5,50		B9903105012B00054

Printing

8x0,50 Comari Alarmkabel 8X0,5 mm MBZH LI-H(st)H B2ca-s1,d0,a1 CE B180987002701 YEAR/LOT 0000m

Office	Date	Signature	Rev.	Date	Signature
Edit by:	08/06/2017	Ufficio Tecnico	3	02/03/2018	
Checked by:	08/06/2017	Laboratorio			