




36040 Meledo di Sarego (Vi) ITALIA
 Tel. +390444-820044 Fax +390444-820050
www.bericacavi.com e-mail: sales@bericacavi.com

Cables for security systems, Al/Pet tape screen, halogen free.

Comari Alarmkabel afgeschermd



CPR Compliant
Cca - s1a,d1,a1

Caratteristiche	Descrizione	Norme
Conductors :	annealed red copper cl.5	CEI EN 60228
Insulation :	LSZH compound	
Cores colour :	white- red- yellow- green- grey- orange-light blue- brown- purple -black (black and red for power supply)	
Assembling :	Pet tape	
Drain wire :	annealed red copper 7x0,20	
Screen :	Al/Pet tape	
Sheath :	LSZH	CEI EN 50363
Sheath colour :	white RAL 9010 or Orange RAL 2004	
Halogen free :	(< 0,5 mg/g - 0,5%)	CEI EN 60754-1/2
Testing voltage :	2000 V	
Max working temperature :	70 °C	
Short circuit temperature :	160 °C	
Min. installation temperature :	0 °C	
Bending radius :	Ø x 8	

APPLICATION : Supply of communications in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.

INSTALLATION: For fixed indoor installation. They can be installed in cable trays, pipes, conduits, and similar systems. They can be laid together with power cables with marking both 450/750V, and 0.6 / 1 kV, used for systems with a nominal voltage to ground (Uo) up to 400 V. Not for direct burial.

Type						Medium	Medium	Product
(N° cores x sect.)						Outer Ø	Weight	code
N° x mm								
4x0,22						3,70	23	B9903105012C00058
6x0,22						4,30	29	B9903105012C00053

Code	Printing
B9903105012C00058	Comari Alarmkabel 4x0,22 MBZH LI-H(st)H Cca-s1a,d1,a1 CE B230987006601 Year/Lot 00000m
B9903105012C00053	Comari Alarmkabel 6x0,22 MBZH LI-H(st)H Cca-s1a,d1,a1 CE B230987006601 Year/Lot 00000m

Office	Date	Signature	Rev.	Date	Signature
Edit by :	31/10/2023		0	31/10/2023	
Checked by:	31/10/2023				