



36040 Meledo di Sarego (Vi) ITALIA  
 Tel. +390444-820044 Fax +390444-820050  
[www.bericacavi.com](http://www.bericacavi.com) e-mail: [sales@bericacavi.com](mailto:sales@bericacavi.com)

Cables for security, telephone and fire detection systems, halogen free.

### Comari Signaalkabel zonder afscherming



**CPR Compliant**  
**B2ca-s1a,d0,a1**

Features	Description	Standards					
<a href="#">Conductors :</a>	annealed red copper cl. 1	CEI EN 60228					
<a href="#">Insulation :</a>	LSZH						
<a href="#">Cores colour :</a>	2x(red-blue); 4x(blue -red-yellow-green); 2x2x(red/white - blue/white) 4x2x (red/white - blue/white - yellow/white - green/white )						
<a href="#">Sheath</a>	LS0H	CEI EN 50363					
<a href="#">Sheath colour :</a>	Grey RAL 7001						
<a href="#">Halogen free :</a>	(< 0,5 mg/g - 0,5%)	CEI EN 50267-2-1/2 - IEC 60754-1/2					
<a href="#">Rated voltage Uo/U :</a>	300/300 V						
<a href="#">Max voltage :</a>	330 V						
<a href="#">Testing voltage :</a>	2000 V						
<a href="#">Max working temperature :</a>	70 °C						
<a href="#">Short-circuit temperature :</a>	160 °C						
<a href="#">Min. installation temperature :</a>	0 °C						
<a href="#">Bending radius :</a>	Ø x 8						
<a href="#">APPLICATION:</a> Supply of communications in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.							
<a href="#">INSTALLATION:</a> For fixed indoor installation. They can be installed in platforms, pipes, conduits and similar systems. Not for direct burial.							
Type					Medium Ø	Medium	Product
(N° cores x Ø)					outer	weight	code
N° x mm					mm	kg x km	
1x2x0,80					4,30	24	B9903105012B00020
4x0,80					4,90	39	B9903105012B00021
Code		Printing					
B9903105012B00020		Comari Signaalkabel 2x0,8 mm MBZH J-HH B2ca-s1a,d0,a1 CE B200987004801 Year/Lot 00000m					
B9903105012B00021		Comari Signaalkabel 4x0,8 mm MBZH J-HH B2ca-s1a,d0,a1 CE B200987004801 Year/Lot 00000m					
Office		Date	Signature	Rev.	Date	Signature	
Edit by :				0			
Cheked by:							