




36040 Meledo di Sarego (Vi) ITALIA
 Tel. +390444-820044 Fax +390444-820050
www.bericacavi.com e-mail: sales@bericacavi.com

Cables for security, telephone and fire detection systems, Al/Pet tape screen, halogen free.

Comari Signaalkabel afgeschermd



CPR Compliant
B2ca-s1a,d0,a1

Features	Description	Standards
Conductors :	annealed red copper cl. 1	CEI EN 60228
Insulation :	LSZH	
Cores colour :	2x(red-blue); 4x(blue -red-yellow-green); 2x2x(red/white - blue/white) 4x2x (red/white - blue/white - yellow/white - green/white)	
Assembling :	Pet tape	
Drain wire :	annealed red copper 1x0,50 mm	
Screen :	Al/Pet tape	
Sheath	LSZH	CEI EN 50363
Sheath colour :	Grey RAL 7001	
Halogen free :	(< 0,5 mg/g - 0,5%)	CEI EN 50267-2-1/2 - IEC 60754-1/2
Rated voltage Uo/U :	300/300 V	
Max voltage :	330 V	
Testing voltage :	2000 V	
Max working temperature :	70 °C	
Short-circuit temperature :	160 °C	
Min. installation temperature :	0 °C	
Bending radius :	Ø x 8	

APPLICATION: Supply of communications in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.

INSTALLATION: For fixed indoor installation. They can be installed in platforms, pipes, conduits and similar systems. Not for direct burial.

Type (N° cores x Ø)						Medium outer Ø	Medium weight	Product code
N° x mm						mm	kg x km	
1x2x0,80						4,40	31	B9903105012B00017
2x2x0,80						6,50	61	B9903105012B00018
4x2x0,80						8,00	96	B9903105012B00019

Code	Printing
B9903105012B00017	Comari Signaalkabel 1x2x0,8 mm MBZH J-H(ST)H B2ca-s1a,d0,a1 CE B200987004701 Year/Lot 00000m
B9903105012B00018	Comari Signaalkabel 2x2x0,8 mm MBZH J-H(ST)H B2ca-s1a,d0,a1 CE B200987004701 Year/Lot 00000m
B9903105012B00019	Comari Signaalkabel 4x2x0,8 mm MBZH J-H(ST)H B2ca-s1a,d0,a1 CE B200987004701 Year/Lot 00000m

Office	Date	Signature	Rev.	Date	Signature
Edit by :	31/10/2023		0	31/10/2023	
Checked by:	31/10/2023				